RAY GLASS
DYNAMIC

The RAY Lighting Glass bulb is our entry-level lightbulb. Ideal for use in ceilings.

NATURE'S BLUE LIGHT
the sleep better bulb

EYE KIND
kind to eyes & mind

FULLY DIMMABLE
get in the perfect mood

CIRCADIAN FRIENDLY
natural healthy light

APPLICATIONS

Residential: General areas, kitchens, studies, lounge areas, dining rooms, gardens, facades
Architectural: Hotel corridoors, restaurants, bars, galleries, cafés, lobbies
Commercial: Atriums, reception areas, feature lighting

ADDRESS
RAY LIGHTING, UNIT 15, ROCKHAVEN, METZ WAY, GLOUCESTER, GL1 1AJ, UNITED KINGDOM

CONTACT
TEL:03452962753
EMAIL: INFO@RAY.LIGHTING

ADVANTAGES

- BlueBalance light source
- Full spectrum colour rendering phosphor
- Circadian friendly, humancentric output
- Flicker Free Bridging Technology

ELECTRICAL & PHOTOMETRIC DATA

Nominal Wattage (W) 5.2
Nominal Voltage AC 220-240v
Operating Frequency 50/60Hz
Power Factor 0.7
Working Temperature Range -20°C...+40°C
T-Case Maximum 80°C
Starting Time < 0.5 S
SDCM 3 steps
PstLM <0.1
SVM <0.1

OPTICAL DATA

Lumen (lm)	2700K: 345 / 3000K: 355
CRI	97
Efficacy (lm/w)	2700K: 66 / 3000K: 68

OTHER DATA

Lifetime (hours) 25,000 hours
Warranty 3 years

DIMENSIONS



Height (mm)	52
Lens Diameter (mm)	50

TECHNICAL SPECIFICATIONS





CCT	2700K / 3000K
Beam Angle °	36°

PRODUCT OPTIONS

Colour	N/A
Baffle	N/A

ADDRESS
RAY LIGHTING, UNIT 15, ROCKHAVEN, METZ WAY, GLOUCESTER, GL1 1AJ, UNITED KINGDOM

CONTACT
TEL:03452962753
EMAIL: INFO@RAY.LIGHTING